


SunVivo

PM060MW2/PM060MB2

Mono-Crystalline
Photovoltaic Module



290W
~
310W

Power Range

290 ~ 310 Wp



Highly Strengthened Design

Module complies with advanced loading tests to meet 5400 Pa loading requirements



PID-Resistance (up to Diamond Level)

Certified high PID resistance



Superior Weak Light Performance

Improved absorption of long wavelength light



Flammability Test

Low ignitability ensuring fire safety



Resistance to Salt Corrosion and Humidity

Module complies with IEC 61701: Salt Mist Corrosion Testing



Ammonia Test

Reliable in ammonia rich environment



BenQ
Solar

SunVivo PM060MW2/PM060MB2 (290 ~ 310 Wp)

Electrical Data

Typ. Nominal Power P_N	290W	295W	300W	305W	310W
Typ. Module Efficiency	17.8%	18.1%	18.4%	18.7%	19.1%
Typ. Nominal Voltage V_{mp} (V)	32.3	32.6	32.7	32.9	33.1
Typ. Nominal Current I_{mp} (A)	8.99	9.05	9.18	9.28	9.38
Typ. Open Circuit Voltage V_{oc} (V)	39.7	39.8	39.9	40.2	40.5
Typ. Short Circuit Current I_{sc} (A)	9.57	9.63	9.80	9.91	10.02
Maximum Tolerance of P_N	0 / +3%				

- Above data are the effective measurement at Standard Test Conditions (STC)
- STC: irradiance 1000 W/m², spectral distribution AM 1.5, temperature 25 ± 2 °C, in accordance with EN 60904-3
- Black back sheet (PM060MB2) is utilized for 290 & 300W; white back sheet (PM060MW2) is for 295-310W

Temperature Coefficient

NOCT	46 ± 2 °C
Typ. Temperature Coefficient of P_N	-0.42 % / K
Typ. Temperature Coefficient of V_{oc}	-0.30 % / K
Temperature Coefficient of I_{sc}	0.05 % / K

- NOCT: Normal Operation Cell Temperature, measuring conditions: irradiance 800 W/m², AM 1.5, air temperature 20 °C, wind speed 1 m/s

Mechanical Characteristics

Dimensions (L x W x H)	1640 x 992 x 40 mm (64.57 x 39.05 x 1.57 in)
Weight	19 kg (41.89 lbs)
Front Glass	High transparent solar glass (tempered), 3.2 mm (0.13 in)
Cell	60 monocrystalline solar cells
Back Sheet	Composite film
Frame	Anodized aluminum frame
Junction Box	IP-67 rated with 3 bypass diodes
Connector Type & Cables	TE Connectivity PV4: 1 x 4 mm ² (0.04 x 0.16 in ²), Length: each 1.0 m (39.37 in)

Operating Conditions

Operating Temperature	-40 ~ +85 °C
Ambient Temperature Range	-40 ~ +45 °C
Max. System Voltage IEC/UL	1000 V / 1000 V
Serial Fuse Rating	15 A
Maximum Surface Load Capacity	Tested up to 5400 Pa according to IEC 61215 (advanced test)

Warranties and Certifications


Product Warranty	Maximum 12 years for material and workmanship
Performance Guarantee	Guaranteed linear degradation to 80% for 25 years *1
Certifications	According to IEC/EN 61215, IEC/EN 61730 and UL 1703 guidelines *2

- *1: Please refer to warranty letter for detail
- *2: Please confirm other certifications with official dealers


Packing Configuration

Container	20' GP	40' GP	40' HQ
Pieces per Pallet	26	26	26
Pallets per Container	6	14	28
Pieces per Container	156	364	728

Dimensions mm (inch)



I-V Curve



Current/voltage characteristics with dependence on irradiance and module temperature.



Dealer Stamp



AU Optronics Corporation

No. 1, Li-Hsin Rd. 2, Hsinchu Science Park, Hsinchu 30078, Taiwan
Tel: +886-3-500-8899 www.BenQSolar.com



BenQ Solar is a division of AU Optronics This datasheet is printed with Soy Ink
© Copyright September 2015 AU Optronics Corp. All rights reserved. Information may change without notice.



BenQ
Solar