

HS912S - Smart Wireless Home Alarm Kit with Camera



KEY FEATURES AND BENEFITS

- Honeywell unique patented bi-directional secure 868 MHz Wireless Technology - longer range (1000m) and improved battery performance.
- Standard SIM Card with roaming services.
- Ethernet port for IP connection.
- Up to 32 peripherals per installation.
- Leave your home with complete peace of mind. The APP allows you to monitor your home from a tablet or smartphone to ensure your family is safe
- Total Connect Comfort International mobile Apps enable visual verification feature which allows you to see what is happening if an alarm is activated. The home owner is notified by SMS or email and can distinguish whether an intrusion has occurred or if it is a false alarm.
- Stand-by 24hrs back up in case of mains loss.
- Total Connect Comfort iOS and Android app available in App Store and Google Play to download. Apps support all security related functions
- Web portal URL to support registration and setup: <https://international.mytotalconnectcomfort.com>

KIT CONTENTS

- 1 x Wireless Hub
- 1 x Wireless Motion Sensor with Colour Camera
- 2 x Wireless Door Window Sensor
- 1 x Wireless Contactless Tag Reader with built-in Siren
- 2 x Contactless tags
- 1 x Ethernet / LAN cable
- 1 x Universal Power Adaptor with EU and UK plug

- All required batteries
- All required fixings
- 1 x Quick start installation guide
- 1 x SMS activation code card
- 1 x Safety and guarantee guide
- 1 x Declaration of conformity



INSTALLATION




- Internal use only.

PRODUCT SPECIFICATION

Languages covered –
GB, DE, FR, ES, PT, IT, NL = English, German, French, Spanish, Portuguese, Italian, Dutch

- Frequency - 868MHz
- Wireless Range : 1000m (open field)
- Operating Temperature: -10°C to +55°C

	<p>Wireless Hub – Ref: SUE8EU-STD-E</p> <ul style="list-style-type: none"> • Comes with free e-mail notification services • Up to 32 peripherals per installation • Ethernet port for IP connection • Supervision • LED System information reports • Power supply 230V~ to DC 6.5V/2A (4 x AA rechargeable batteries (supplied not fitted)) • Stand-by 24h (in case of mains loss) • Low Battery Signaling • Dimensions 190 x 123 x 35 mm
	<p>Wireless Motion Sensor with Colour Camera – Ref : CAMIR-8EZS</p> <ul style="list-style-type: none"> • Colour images • 11 x 12m detection range • Night vision LED • Pet immunity • Built in temperature alarm sensor (54°C) • 2 x CR123A battery with approx. 4 years life. Supplied fitted with battery isolation tab • Dimensions 55 x 121 x 64 mm

	<p>Wireless door window sensor Ref : DO8EZS</p> <ul style="list-style-type: none"> • 1 x CR123A with approx. 5 years life. Supplied fitted with battery isolation tab • Dimensions 102 x 22 x 23 mm
	<p>Wireless Contactless Tag Reader Ref. : SPR-S8EZ</p> <ul style="list-style-type: none"> • Up to 10 users • Two buttons • Built-in siren 78dBA @1m • Four LEDs for status • 3 x CR123A with approx. 4 years life. Supplied fitted with battery isolation tab • Dimensions 110 x 110 x 30 mm
	<p>Contactless tags Ref. : TAG4</p> <ul style="list-style-type: none"> • 2 black • Dimensions 47 x 30 x 3 mm

PACKAGING DATA

SINGLE PRODUCT

EAN code: 5004100969408

Weight: approx. 2500g

Pack dimension: 160 x 320 x 160mm

STANDARD PACK

Quantity: 4